TECHNICAL DATA SHEET

Customer:				Ref.:			
Item		Quantity		Required flow	n.d.	Required head	n.d.
Type	SUBMERSIBLE ELECTRIC PUMP			Model	**E10PX250/8A+MW14330-8V**		





Dimensions [mm]

A	4067	**E**	337				
B	2085	**F**	G6"				
C	1982	**G**	426				
D	235	**Ø max**	340				

OPERATING DATA- ISO 9906:2012 3B -

Q [l/s]	H [m]	P [kW]	η [%]	NPSH [m]

CONSTRUCTION CHARACTERISTICS

Delivery diameter	G6"	n.d.
Max. overall diameter	340	mm
Weight of electric pump	1037	Kg
No. Stages	8	
Motor seal	Mechanical	
Type of installation	Vertical	

OPERATING LIMITS

Pumped liquid	Water	
Max. temp. of pumped liquid (*)	25	°C
Maximum density	1	kg/dm³
Maximum viscosity	1	mm²/s
Maximum solid content	150	g/m³
Max. number of starts/hr	3	
Minimum immersion depth	850	mm

OPERATING CHARACTERISTICS

Service flow rate		n.d.		n.d.
Service head		n.d.		n.d.
Qmin	Qmax	32.5	90	l/s
H (Q=0)	Hmax (Qmin)	369.42	329.61	m
Power consumption at duty point		n.d.		n.d.
Pump efficiency	Overall efficiency	n.d.	n.d.	n.d.
Max. pump efficiency (B.E.P.)		79.2		n.d.
Sense of rotation (**)		Anticlockwise		
Number of pumps installed		Operating		Stand-by
		1		0

ELECTRIC MOTOR CHARACTERISTICS

Nominal power		240		kW
Rated frequency		50		Hz
Rated voltage		400		V
Rated current		453.4		A
No. Poles	Nominal speed	2	2955	1/min
Insulation class	Protection class	n.d.		IP68
Certified motor for use with drinking water				

PUMP MATERIALS

Diffuser unit	Stainless steel
Suction casing	Stainless steel
Impeller	Stainless steel
Shaft	Stainless steel
Coupling	
Pump shaft bearing bush	Stainless steel/rubber
Valve casing	Stainless steel
Strainer	Stainless steel
Wear ring	Stainless steel/rubber

MOTOR MATERIALS

Shaft	Stainless steel
Upper bracket	Stainless steel
Rotor	Electrical steel
Stator	Electrical steel
Stator shell	Stainless steel
Winding	PE2+PA
Lower bracket	Stainless steel
Mechanical seal	Silicon carbide/silicon carbide
Bearing bush	Bronze
Thrust-bearing	Brass/Synthetic compound
Thrust-bearing foot slip	Nodular cast iron
Diaphragm	Rubber
Shaft sleeve	Chrome plated steel
Motor bracket	Stainless steel

Notes:

(*) Speed of the water outside the jacket of the motor v=0.3 m/s

(**) View from delivery port.

In case of VSD operation, refer to Use and Maintenance Instructions of the electric pump.

OFFER No.	Pos.	Date 14/01/2020

T400IT-V01